



US010035110B2

(12) **United States Patent**
Wu et al.

(10) **Patent No.:** **US 10,035,110 B2**
(45) **Date of Patent:** **Jul. 31, 2018**

- (54) **FINE BUBBLE GENERATING DEVICE**
- (71) Applicant: **Chao-Chung Wu, Taichung (TW)**
- (72) Inventors: **Chao-Chung Wu, Taichung (TW); Yu-Lung Tsai, Taichung (TW)**
- (73) Assignee: **Chao-Chung Wu, Taichung (TW)**
- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 196 days.

- 3,605,388 A * 9/1971 Zuiderweg et al. B01D 3/26
261/114.1
- 3,953,002 A * 4/1976 England, Jr. B01F 3/10
261/76
- 5,938,982 A * 8/1999 Sugiura B01F 3/04503
261/75
- 6,027,241 A * 2/2000 King B01F 3/0873
138/38
- 7,510,172 B2 * 3/2009 Kojima B01D 53/18
261/113
- 7,624,969 B2 * 12/2009 Schletz A01K 63/042
261/36.1
- 7,797,937 B2 * 9/2010 Endicott F02B 29/0468
123/306
- 8,826,649 B2 * 9/2014 Li F01N 3/2892
138/37

(21) Appl. No.: **15/135,927**

(22) Filed: **Apr. 22, 2016**

(65) **Prior Publication Data**

US 2017/0304782 A1 Oct. 26, 2017

- (51) **Int. Cl.**
B01F 3/04 (2006.01)
B01F 5/04 (2006.01)

- (52) **U.S. Cl.**
CPC **B01F 3/04248** (2013.01); **B01F 5/0425**
(2013.01); **B01F 2003/04276** (2013.01); **B01F**
2003/04319 (2013.01)

- (58) **Field of Classification Search**
CPC .. **B01F 3/04248**; **B01F 5/0415**; **B01F 5/0425**;
B01F 2003/04276; **B01F 2003/04319**
USPC 261/79.2
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

- 847,552 A * 3/1907 Carlson F28F 25/082
222/394
- 3,567,116 A * 3/1971 Lindlof B01F 5/0415
239/14.2

(Continued)

FOREIGN PATENT DOCUMENTS

TW M424358 U 3/2012

Primary Examiner — Charles Bushey
(74) *Attorney, Agent, or Firm* — Muncy, Geissler, Olds & Lowe, P.C.

(57) **ABSTRACT**

A fine bubble generating device is provided, including: a main body, having an inlet, an outlet and a venturi tube mechanism located between the inlet and the outlet, the venturi tube mechanism having a neck portion communicating with outside; a bubble fining mechanism, having at least one passage which is smaller than the inlet in cross-sectional area, the at least one passage communicating with and between the venturi tube mechanism and the outlet. The bubble fining mechanism includes a first vortex member having at least one first slant hole and a second vortex member having at least one second slant hole. The at least one first slant hole and the at least one second slant hole are inclined toward opposite directions, and the first vortex member and the second vortex member is disposed between the venturi tube mechanism and the outlet.

11 Claims, 7 Drawing Sheets